



TECHNICAL SHEET

IVECO TRAKKER AD-AT 260T & 380T 6x4 into 8x4 configuration 1+3 rear steer – GVW 32 ton (tech. max. 36 ton)



DESCRIPTION

The above four axle configuration is achieved by the application of an **original Iveco steering tag axle** to the base 6x4 vehicle. The base model can be either a **TRAKKER AD/AT 260** or an **AD/AT 380**. The added axle is fitted with an independent full command hydraulic steering system. It also benefits from an axle lift and automatic drop function.

TECHNICAL NOTE

- Original Iveco steering axle (7186386) mounted.
- Base vehicle can have either original pneumatic or mechanical drive axle suspension.
- Rear axle is fitted with pneumatic suspension.
- Patented hydraulic steering system with automatic self-centering in emergency condition.
- S.T. System Truck designed engine to hydraulic pump interface.
- Fully automatic axle lift and drop function.
- Homologated tyre size range includes 315/80 R22.5, 13 R22.5 and 385/65 R22.5.
- Conversion (incl. tyres + overhang extension) increases the vehicle weight by 1050 kg.
- European Whole Vehicle Type Approval (EWVTA) for second stage body builder.

For further information contact S.T. SYSTEM TRUCK S.p.A. 0039.0376.696809 or info@stsystemtruck.com